

## SAFETY DATA SHEET

# VAPOR BARRIER

## PART A

### 1. PRODUCT IDENTIFICATION


<b>TRADE NAME (AS LABELED):</b>	VAPOR BARRIER
<b>SUPPLIER/MANUFACTURER'S NAME:</b>	LEGGARI PRODUCTS, LLC
<b>ADDRESS:</b>	3105 E AINSWORTH AVE WAREHOUSE 5, BAY 2 PASCO, WA 99301
<b>INFORMATION TELEPHONE:</b>	714-694-2061
<b>EMERGENCY TELEPHONE:</b>	800-255-3924

### 2. HAZARD(S) IDENTIFICATION

#### GHS RATINGS

Skin corrosion:	Category 2
Skin sensitization:	Category 1
Serious eye damage:	Category 2
Germ cell mutagenicity:	Category 2
Reproductive toxicity:	Category 1B
Specific target organ toxicity (single exposure):	Category 1
Specific target organ toxicity:	Category 1
Acute aquatic toxicity:	Category 2
Chronic aquatic toxicity:	Category 2

#### SIGNAL WORD: WARNING



**PREVENTION:** Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash before reuse. Avoid release to the environment. Collect spillage.

## RESPONSE

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

## STORAGE

Keep container tightly closed and locked in a cool, well-ventilated place.

## DISPOSAL

Dispose of contents/container to an approved waste disposal plant in accordance with applicable laws and regulations, and product characteristics at time of disposal.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Oxirane, 2, 2'-((1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-,homopolymer	25085-99-8	50% - 60%

# 4. FIRST AID MEASURES

## GENERAL ADVICE

Seek medical advice or medical attention if condition persists.

**INHALATION:** Move victims into fresh air. If breathing is labored, administer oxygen. If not breathing, give artificial respiration. Consult a doctor immediately.

**INGESTION:** Rinse out mouth, spit out liquid. Do not induce vomiting and seek medical advice immediately. Never give anything by mouth to an unconscious person.

**NOTES TO PHYSICIAN:** No specific treatment. Treat symptomatically. Call the poison control center immediately if large quantities have been ingested.

**EYE CONTACT:** Rinse immediately with plenty of water for 15 minutes and seek advice of an eye specialist/physician. Continue rinsing eyes during transport to hospital. Do not remove contact lens if worn.

**SKIN CONTACT:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Take victim immediately to hospital to obtain medical attention. Destroy or thoroughly clean contaminated shoes before reuse.

# 5. FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical, carbon dioxide, dry sand.

**EXPOSURE HAZARD:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Explosion hazards noted. Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Combustible liquid and vapor.

**SPECIAL FIREFIGHTING PROCEDURES:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**DANGER OF EXPLOSION:** This product does not present an explosion hazard

**FLAMMABLE LIMITS:** Not Available

**EXPLOSION LIMITS:** Not Available

**AUTO-IGNITION:** Not Available

**FLASH POINT:** >200°C (>392°F) [DIN 51758 EN 22719 (Pensky-Martens Closed Cup)]

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**ENVIRONMENTAL PRECAUTIONS:** Water polluting material. May be harmful to the environment if released in large quantities. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform authorities if the product has caused environmental pollution (sewers, drains, waterways or soil).

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: See Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. HANDLING AND STORAGE

### **PRECAUTION FOR SAFE HANDLING:**

Put on appropriate personal protective equipment, PPE (see Section 8). Eating and drinking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated PPE or clothing, wash hands and face before eating and drinking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Use only in area provided with appropriate exhaust ventilation. Empty containers retain product residue and can be hazardous. Do not get in eyes, skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment.

### **CONDITIONS FOR SAFE STORAGE:**

Store between 4 to 26°C (40 to 80°F) in accordance with local regulations away from sources of heat, ignition, and direct sunlight. Store in original container. Keep in a dry, well-ventilated area, and away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled or unapproved containers. Use appropriate containment to avoid environmental contamination.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **SPECIAL NOTE FOR EXPOSURE CONTROL:**

Consult local authorities for acceptable exposure limits.  
EXPOSURE GUIDELINES OSHA PEL (TWA): Not Determined  
ACGIH TLV (TWA): Not Determined  
NIOSH REL (TWA): Not Determined

### **INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT**

**ENGINEERING CONTROLS:** No special ventilation requirements. If possible work in ventilated area. Provide natural or explosion-proof fan to ensure adequate ventilation, especially in confined area. Avoid contact with skin, eyes, and clothing.

**ENVIRONMENTAL EXPOSURE CONTROLS:** Construct a dike to prevent spreading. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**HYGIENIC PRACTICES:** Wash hands, forearms and face thoroughly after handling chemical products, before eating and drinking, smoking or using the lavatory and at the end of the working period. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**RESPIRATORY PROTECTION:** In case of inadequate ventilation wear VAPOR respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**OTHER PROTECTIVE EQUIPMENT:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Neoprene gloves. PVC disposable gloves. Nitrile rubber. Butylrubber. Impervious gloves. (The breakthrough time of the selected glove(s) must be greater than the intended use period.)

**EYE PROTECTION:** Splash proof safety glasses.

**SKIN PROTECTION:** Neoprene rubber or plastic apron. Neoprene rubber or plastic gloves. Long sleeved clothing or wear protective sleeves. Remove and wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid	Odor : Faint
Odor threshold : N/A	PH : Neutral
Melting point : N/A	Boiling point : 212°F
Flash Pt (F/C) : N/A	Evaporation rate : N/A
Flammability (solid, gas) : N/A	LEL/UEL : N/A
Vapor pressure : 19.30 mm Hg at 70°F (21°C)	Vapor density : N/A
Relative density : N/A	Solubility : Insoluble
Naphtha, petroleum, heavy alkylate	Autoignition temp : N/A
Partition coefficient:n- N/A octanol/water :	Viscosity : N/A
Decomposition temp : N/A	VOC: <1 g/L

## 10. STABILITY AND REACTIVITY

**CHEMICAL STABILITY:** Stable under normal conditions. Hazardous reactions will not occur.

**CONDITIONS TO AVOID:** No specific data.

**SUBSTANCES TO BE AVOIDED:** Strong acids, strong bases, strong oxidizing agents.

**HAZARDOUS DECOMPOSITION:** Under normal conditions hazardous decomposition products should not be produced.

**HAZARDOUS POLYMERIZATION:** Under normal conditions hazardous polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

Toxicity Studies:

Acute Oral Toxicity:

Acute Dermal Toxicity:

Medical Conditions Aggravated by Overexposure:

Bisphenol A-(epichlorhydrin), Bisphenol A epoxy resin

Low toxicity, LD50 >2000 mg/kg.

Low toxicity, LD50 >2000 mg/kg.

Pre-existing skin disorders may be aggravated by over-exposure to this product.

## POTENTIAL CHRONIC HEALTH EFFECTS

**Chromic Effects:** Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Target Organs:** No known significant effects or critical hazards.

**Carcinogenicity:** No known significant effects or critical hazards.

**Mutagenicity:** No known significant effects or critical hazards.

**Teratogenicity:** No known significant effects or critical hazards.

**Developmental Effects:** No known significant effects or critical hazards.

**Fertility Effects:** No known significant effects or critical hazards.

## 12. ECOLOGICAL INFORMATION

### ENVIRONMENTAL EFFECTS

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This product shows a high bioaccumulation potential. Water polluting material. May be harmful to the environment if released in large quantities.

Biodegradability Studies: Bisphenol A-(epichlorhydrin), Bisphenol A epoxy resin

TEST	RESULT	DOSE	INOCULUM
OECD Derived from OECD 301F (Biodegradation Test)	5%-Not Readily 28 days	20 mg/L Oxygen consumption	No Data

## 13. DISPOSAL CONSIDERATION

Waste should be disposed of according to local, state, and federal regulations.

The generation of waste should be avoided or minimized wherever possible. Empty containers should be taken to an approved waste handling site for recycling or disposal. Incineration or landfill should only be considered when recycling is not feasible. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## 14. TRANSPORT INFORMATION

This material is classified for transport as follows:

<b>AGENCY</b>	<b>Proper Shipping Name</b>	<b>UN Number</b>	<b>Packing Group</b>	<b>Hazard Class</b>
DOT	Non-Regulated Material	Non-Regulated	Non-Regulated	Non-Regulated
IMO/IMDG	Non-Regulated Material	Non-Regulated	Non-Regulated	Non-Regulated
IATA/CAO	Non-Regulated Material	Non-Regulated	Non-Regulated	Non-Regulated

## 15. REGULATORY INFORMATION

COUNTRY	REGULATORY LIST	NOTIFICATION
USA	TSCA	Included on inventory
EU	EINECS	Included on inventory
Canada	DSL	Included on inventory
China	SEPA	Included on inventory
Japan	ENCS	Included on inventory

**OSHA:** This product is considered to be a hazardous chemical under 29 CFR 1910.1200.

**OSHA/HCS Classification:** Irritating material, Sensitizing material.

**SARA 302/304/311/312 extremely hazardous substances:** No ingredients listed.

**SARA 311/312 Hazard Identification:** No ingredients listed.

**SARA 313 Hazard Identification:** No ingredients listed.

**California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) - WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer. This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

<u>Ingredient Name</u>	<u>Cancer</u>	<u>Reproductive</u>	<u>No Significant Risk Level</u>	<u>Maximum Acceptable Dosage Level</u>
1-chloro-2,3-epoxypropane CAS: 106-89-8	Yes	Yes	Yes	No

**Canada WHMIS:** Class D2B: Material causing other toxic effects.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contain all the information required by the Controlled Products Regulations

## 16. OTHER INFORMATION

### HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS)

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	X

4. Severe Hazard
3. Serious Hazard
2. Moderate Hazard
1. Slight Hazard
0. Minimal Hazard

**Personal Protection:** Safety goggles, neoprene rubber gloves, vapor respirator

Leggari Products, LLC believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Leggari Products, LLC makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

## SAFETY DATA SHEET

# VAPOR BARRIER

## PART B

### 1. PRODUCT IDENTIFICATION

**TRADE NAME (AS LABELED):**

VAPOR BARRIER

**SUPPLIER/MANUFACTURER'S NAME:**

LEGGARI PRODUCTS, LLC

**ADDRESS:**

3105 E AINSWORTH AVE

WAREHOUSE 5, BAY 2

PASCO, WA 99301

**INFORMATION TELEPHONE:**

714-694-2061

**EMERGENCY TELEPHONE:**

800-255-3924

### 2. HAZARD(S) IDENTIFICATION

#### GHS RATINGS

Skin corrosion:	Category 1C
Skin sensitization:	Category 1
Serious eye damage:	Category 1
Germ cell mutagenicity:	Category 2
Reproductive toxicity:	Category 1B
Specific target organ toxicity (single exposure):	Category 1
Specific target organ toxicity:	Category 1
Acute aquatic toxicity:	Category 1
Chronic aquatic toxicity:	Category 1

**SIGNAL WORD: DANGER**



**PREVENTION:** Do not eat, drink, or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, and eye and face wear. Avoid release to the environment. Collect spillage.

## RESPONSE

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

## STORAGE

Keep container tightly closed and locked in a cool, well-ventilated place.

## DISPOSAL

Dispose of contents/container to an approved waste disposal plant in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**OTHER INFORMATION:** Not known.

**GENERAL INFORMATION:** This product contains no listed carcinogens according to IARC, ACGIH, NTP, and/or OSHA in concentrations of 0.1 percent or greater. Repeated or prolonged contact causes sensitization, asthma, and eczemas.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Chemical Name	CAS number	Weight Concentration %
Alkylphenol	Trade Secret	30-45
Aliphatic Amine	Trade Secret	20-25
Isophorone Diamine	Trade Secret	20-25
Alkyletheramine	Trade Secret	10-15
Phenol, 4-Nonyl-, Branched	84852-15-2	6-10
Alkyl Amine	Trade Secret	4-10
Benzyl Alcohol	Trade Secret	5-15

## 4. FIRST AID MEASURES

### GENERAL ADVICE

Seek medical advice or medical attention if condition persists.

**INHALATION:** Move victims into fresh air. If breathing is labored, administer oxygen. If not breathing, give artificial respiration. Consult a doctor immediately.

**INGESTION:** Rinse out mouth, spit out liquid. Do not induce vomiting and seek medical advice immediately. Never give anything by mouth to an unconscious person.

**NOTES TO PHYSICIAN:** No specific treatment. Treat symptomatically. Call the poison control center immediately if large quantities have been ingested.

**EYE CONTACT:** Rinse immediately with plenty of water for 15 minutes and seek advice of an eye specialist/physician. Continue rinsing eyes during transport to hospital. Do not remove contact lens if worn.

**SKIN CONTACT:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Take victim immediately to hospital to obtain medical attention. Destroy or thoroughly clean contaminated shoes or clothing before reuse.

## 5. FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Water spray, alcohol-resistant foam, CO2, dry powder.



**UNSUITABLE EXTINGUISHING MEDIA:** High volume water jet.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Firefighters should wear NFPA approved self-contained breathing apparatus and full protective clothing. Avoid contact with product. Decontaminate equipment and protective clothing prior to re-use. Toxic and irritating gases/fumes may be given off during burning or thermal decomposition.

**HAZARDOUS DECOMPOSITION PRODUCTS:** On combustion, toxic gases, including nitrogen oxides, carbon monoxide, carbon dioxide, tin/tin oxides.

**ADVICE TO FIRE FIGHTERS:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture. Toxic gases/fumes may be given off during burning or thermal decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**ENVIRONMENTAL PRECAUTIONS:** Water polluting material. May be harmful to the environment if released in large quantities. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform authorities if the product has caused environmental pollution (sewers, drains, waterways or soil).

**METHODS FOR CLEAN-UP:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: See Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. HANDLING AND STORAGE

### **PRECAUTION FOR SAFE HANDLING:**

Put on appropriate personal protective equipment, PPE (see Section 8). Eating and drinking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated PPE or clothing, wash hands and face before eating and drinking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Use only in area provided with appropriate exhaust ventilation. Empty containers retain product residue and can be hazardous. Do not get in eyes, skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment.

### **CONDITIONS FOR SAFE STORAGE:**

Store between 4 to 26°C (40 to 80°F) in accordance with local regulations away from sources of heat, ignition, and direct sunlight. Store in original container. Keep in a dry, well-ventilated area, and away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled or unapproved containers. Use appropriate containment to avoid environmental contamination.

### **INCOMPATIBLE MATERIALS OR IGNITION SOURCES:**

Stable under recommended storage conditions. Do not store together with oxidizing and acidic materials. Do not store together with caustic solutions and alkalis. Store away from food. Avoid water, air humidity, oxidizing agents, cotton waste or other combustible materials. Keep away from sources of ignition - No smoking. Additional guidance on fire and explosion protection may be found in various consensus standards, including NFPA 30, 69 and 77 and API 2003 as well as OSHA regulation 29CFR1910.106.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**SPECIAL NOTE FOR EXPOSURE CONTROL:** Consult local authorities for further acceptable exposure limits.

Chemical Name	RESULT	ACGIH/OSHA
Aliphatic Amine	STEL	N/A
	TWA	0.100000 mg/m <sup>3</sup> (OSHA, ACGIH, NIOSH)
	PEL	N/A

**ENGINEERING CONTROLS:** General dilution and local exhaust as necessary to control airborne vapors, mists, dusts, and thermal decomposition products below appropriate airborne concentration standards and guidelines. A safety shower and eye wash fountain should be readily available. To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination. Curing ovens must be ventilated to prevent the build-up of explosive atmospheres and to prevent off-gases from entering the workplace.

**ENVIRONMENTAL EXPOSURE CONTROLS:** Avoid release to the environment. Construct a dike to prevent spreading of spills. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters, or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**HYGIENIC PRACTICES:** Wash hands, forearms, and face thoroughly after handling chemical products, before eating and drinking, smoking, or using the lavatory, and at the end of the working period. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Keep away from foodstuffs, beverages, and feed.

**RESPIRATORY PROTECTION:** In case of inadequate ventilation, wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use positive pressure supplied air respirator when airborne concentrations are not known, when airborne levels are 10 times the appropriate TLV, and when spraying is performed or product is applied by aerosol in a confined space or area with limited ventilation. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Contact health and safety professional or manufacturer for specific information.

**EYE/FACE PROTECTION:** Use chemical-resistant goggles. Chemical safety goggles in combination with a full face shield (8-inch minimum) must be used if a splash hazard exists. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU). Contact lenses should not be worn.

**HANDS:** Use permeation resistant gloves such as neoprene or nitrile. The glove must be impermeable and resistant to the product/the substance/the preparation. Selection of the glove material does not only depend on the material, but also on its quality and varies from manufacturer to manufacturer. The resistance of the glove material and manufacture must be determined in advance of the application/use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**SKIN PROTECTION:** Wear rubber or plastic apron and permeation-resistant clothing, chemical-resistant gloves, and long-sleeved shirts, and pants. Gloves must be inspected prior to use. Remove and wash contaminated clothing before reuse.

**GENERAL HYGIENE CONSIDERATIONS:** Keep away from food and drink. Wash hands and face after use. Educate and train workers in the safe use and handling of this product. Emergency showers and eye wash stations should be available. Follow all label instructions.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid, Amber Volatile Organic Compounds: <1 g/L Boiling point : 212°F LEL/UEL : N/A Vapor pressure (25°C) : < 5.00 mmHg at 70 °F (21 °C) Density(nominal): 68.047 lb/ft3 (1.09 g/cm3) at 70 °F (21 °C)	Odor : Characteristic amine Melting point : N/A Evaporation rate : N/A Autoignition temp : N/A Vapor density : N/A Solubility in water : Soluble >500g/L
---	---

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** No data available.

**CHEMICAL STABILITY:** Stable under recommended storage conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** May react with catalysts, oxidizing agents, peroxides, strong alkali and other radical forming substances.

**CONDITIONS TO AVOID:** Avoid oxidizing agents.

**INCOMPATIBLE MATERIALS:** Strong bases, strong oxidizing agents.

**HAZARDOUS DECOMPOSITION:** Carbon monoxide, carbon dioxide, and nitrogen oxides.

## 11. TOXICOLOGICAL INFORMATION

**For aliphatic amine:**

LD50 Oral Rat 1040 mg/kg (OCED Test Guideline 401)

LC50 Inhalation Rat 2.4 mg/l (4h)

**For Alkyletheramine:**

LD50 Oral Rat 1030 mg/kg (OCED Test Guideline 401)

**For Isophorone Diamine:**

LD50 Oral Rat 1,030 mg/kg

**Other Information:**

On the skin: Caustic effect on skin and mucous membranes.

On the eye: Strong caustic effect.

**Sensitization:**

Sensitization possible through skin contact.

Sensitizing effect through inhalation is possible by prolonged and repeated exposure.

**CARCINOGENICITY**

This product does not contains a component that is classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification: IARC, NTP, and OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen.

**REPRODUCTIVE TOXICITY:** Presumed human reproductive toxicant.

**SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE:** No data available.

**SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE:** No data available.

**ASPIRATION HAZARD:** No data available.

**ADDITIONAL INFORMATION:** RTECS: WH7000000.

TO THE BEST OF OUR KNOWLEDGE THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN THOROUGHLY INVESTIGATED.

**Toxicity Studies:** Bisphenol A-(epichlorhydrin), Bisphenol A epoxy resin

**Acute Oral Toxicity** - Low toxicity, LD50 >2000 mg/kg.

**Acute Dermal Toxicity** - Low toxicity, LD50 >2000 mg/kg.

**Medical Conditions Aggravated by Overexposure:** Pre-existing skin disorders may be aggravated by over-exposure to this product.

## 12. ECOLOGICAL INFORMATION

### **Toxicity**

This product is harmful to the environment. Very toxic to fish and other aquatic life with long-lasting effects.

### **Persistence and degradability**

According to the results of tests of biodegradability, this product is partly biodegradable

### **Bioaccumulative potential**

Although the product is partly biodegradable, significant residuals remain

### **Other adverse effects**

No data available.

## 13. DISPOSAL CONSIDERATION

**Waste Disposal:** Dispose in accordance with federal, state, and local regulations.

The generation of waste should be avoided or minimized wherever possible. Empty containers should be taken to an approved waste handling site for recycling or disposal. Incineration or landfill should only be considered when recycling is not feasible. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers).

**Empty Container Precautions:** Dispose of as unused product. Do not heat or cut container with electric or gas torch. Recondition or dispose of empty container in accordance with governmental laws and regulations. Do not reuse empty container without proper cleaning. Label precautions also apply to this container when empty.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.

## 14. TRANSPORT INFORMATION

### **DANGER**



AGENCY	UN NUMBER	UN PROPER SHIPPING NAME	TRANSPORT HAZARD CLASS	PACKING GROUP	ENVIRONMENTAL HAZARDS
DOT	UN2735	Polyamines, liquid, corrosive, n.o.s. (Isophorone Diamine)	8	III	MARINE POLLUTANT
IMO/IMDG	UN2735	Polyamines, liquid, corrosive, n.o.s. (Isophorone Diamine)	8	III	MARINE POLLUTANT
IATA/CAO	UN2735	Polyamines, liquid, corrosive, n.o.s. (Isophorone Diamine)	8	III	MARINE POLLUTANT

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

## 15. REGULATORY INFORMATION

COUNTRY	REGULATORY LIST	NOTIFICATION
USA	TSCA	listed/registered
EU	EINECS	listed/registered
Canada	DSL	listed/registered
China	SEPA	listed/registered
Japan	ENCS	listed/registered

### US Federal Regulations

**U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities:** None

**U.S. - SARA - Section 311/312 Hazard Categories:** None

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs:** None

**U.S. - CERCLA/SARA - Section 313 - Emissions Reporting:** None

**U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing:** None

**U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components:** None

**U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 372.65) Supplier Notification Required Components:** None

**U.S. Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):** Under RCRA it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

### U.S. State Regulations

**California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) WARNING:** This product can expose you to parachlorobenzotrifluoride (PCBTF), which is known to the State of California to cause cancer.

Based on information provided by Kretus suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716, File No. S7-40-10, Date 08-22-212).

## 16. OTHER INFORMATION

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	X

- 4. Severe Hazard
- 3. Serious Hazard
- 2. Moderate Hazard
- 1. Slight Hazard
- 0. Minimal Hazard

**Personal Protection:** Safety goggles, neoprene rubber gloves, vapor respirator

Leggari Products, LLC believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Leggari Products, LLC makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.