
LEGGARI

VAPOR BARRIER

Part B - Safety Data Sheet

Table of Contents

Product Identification	1
Hazard Identification	2
Composition/Information on Ingredients	3
First-Aid Measures	4
Fire-Fighting Measures	5
Accidental Release Measures	6
Handling and Storage	7
Exposure Controls/Personal Protection	8-9
Physical and Chemical Properties	10
Stability and Reactivity	11
Toxicological Information	12
Ecological Information	13
Disposal Considerations	14
Transport Information	15
Regulatory Information	16
Other Information	17



1 | PRODUCT IDENTIFICATION



TRADE NAME (AS LABELED):

LEGGARI VAPOR BARRIER PART B

SUPPLIER/MANUFACTURER'S NAME:

LEGGARI PRODUCTS, LLC

ADDRESS:

**3105 E AINSWORTH AVE
WAREHOUSE 5, BAY 2
PASCO, WA 99301**

TELEPHONE:

1-844-LEGGARI (534-4274)

EMAIL:

CUSTOMERSERVICE@LEGGARI.COM



SKIN CORROSION:	Category 1C	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE):	Category 1
SKIN SENSITIZATION:	Category 1	SPECIFIC TARGET ORGAN TOXICITY:	Category 1
SERIOUS EYE DAMAGE:	Category 1	ACUTE AQUATIC TOXICITY:	Category 1
GERM CELL MUTAGENICITY:	Category 2	CHRONIC AQUATIC TOXICITY:	Category 1
REPRODUCTIVE TOXICITY:	Category 1B		

DANGER

Harmful if swallowed or inhaled. Causes damage to organs through prolonged or repeated exposure and severe skin burns and eye damage. May cause an allergic skin reaction. May damage fertility or the unborn child. Very toxic to aquatic life with long-lasting effects.



PREVENTION

Do not eat, drink, or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, and eye and face wear. Avoid release to the environment. Collect spillage.

IF ON SKIN

Wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice/attention. Take off contaminated clothing and wash before use.

IF IN EYES

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists, get medical advice/attention.

STORAGE

Keep container tightly closed and locked in a cool, well-ventilated place.

DISPOSAL

Dispose of contents/container to an approved waste disposal plant in accordance with applicable laws and regulations, and product characteristics at time of disposal.

OTHER INFORMATION

Not known

GENERAL INFORMATION

This product contains no listed carcinogens according to IARC, ACGIH, NTP, and/or OSHA in concentrations of 0.1 percent or greater. Repeated or prolonged contact causes sensitization, asthma, and eczemas.

- READ THE ENTIRE SDS FOR A MORE THOROUGH EVALUATION OF THE HAZARDS.



THE SPECIFIC CHEMICAL IDENTITY AND/OR EXACT PERCENTAGE (CONCENTRATION) OF A COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

CHEMICAL NAME	CAS NO.	CONCENTRATION (% by Weight)	COMMENTS
Alkylphenol	Trade secret	30-45	See above
Aliphatic Amine	Trade secret	20-25	See above
Isophorone Diamine	Trade secret	20-25	See above
Alkyletheramine	Trade secret	10-15	See above
Phenol, 4-Nonyl-, Branched	84852-15-2	6-10	See above
Alkyl Amine	Trade secret	4-10	See above
Benzyl Alcohol	Trade secret	5-15	See above

•SEE SECTION 11 FOR TOXICOLOGICAL INFORMATION

**GENERAL ADVICE**

Seek medical advice or medical attention if condition persists.

EYE CONTACT

Rinse immediately with plenty of water for 15 minutes and seek advice of an eye specialist/physician. Continue rinsing eyes during transport to hospital. Do not remove contact lenses if worn.

SKIN CONTACT

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Take victim immediately to hospital to obtain medical attention. Destroy or thoroughly clean contaminated shoes or clothing before reuse.

INHALATION

Move victims into fresh air. If breathing is labored, administer oxygen. If not breathing, give artificial respiration. Consult a doctor immediately.

INGESTION

Rinse out mouth, spit out liquid. Do not induce vomiting and seek medical advice immediately. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIAN

No specific treatment. Treat symptomatically. Call the poison control center immediately if large quantities have been ingested.



SUITABLE EXTINGUISHING MEDIA

Water spray, alcohol-resistant foam, CO₂, dry powder.

UNSUITABLE EXTINGUISHING MEDIA

High volume water jet.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Firefighters should wear NFPA approved self-contained breathing apparatus and full protective clothing. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. Toxic and irritating gases/fumes may be given off during burning or thermal decomposition.

HAZARDOUS DECOMPOSITION PRODUCTS

On combustion, toxic gases, including nitrogen oxides, carbon monoxide, carbon dioxide, tin/tin oxides.

ADVICE TO FIRE FIGHTERS

Self-contained breathing apparatus and full protective clothing must be worn in case of fire, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture. Toxic gases/fumes may be given off during burning or thermal decomposition.



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

PERSONAL PRECAUTIONS

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

ENVIRONMENTAL PRECAUTIONS

Water polluting material. May be harmful to the environment if released in large quantities. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Inform authorities if the product has caused environmental pollution (sewers, drains, waterways, or soil).

METHODS FOR CLEANING UP

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Contaminated absorbent material may pose the same hazard as the spilled product.

- Note: see section 1 for emergency contact information and section 13 for waste disposal.



PRECAUTIONS FOR SAFE-HANDLING

Put on appropriate personal protective equipment, PPE (see section 8). Eating and drinking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated PPE or clothing, wash hands and face before eating and drinking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Use only in area provided with appropriate exhaust ventilation. Empty containers retain product residue and can be hazardous. Do not get in eyes, skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment.

CONDITIONS FOR SAFE STORAGE

Store between 4 to 26° C (40° to 80° F) in accordance with local regulations away from sources of heat, ignition, and direct sunlight. Store in original container. Keep in a dry, well-ventilated area, and away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled or unapproved containers. Use appropriate containment to avoid environmental contamination.

INCOMPATIBLE MATERIALS OR IGNITION SOURCES

Stable under recommended storage conditions. Do not store together with oxidizing and acidic materials. Do not store together with caustic solutions and alkalis. Store away from food. Avoid water, air humidity, oxidizing agents, cotton waste or other combustible materials. Keep away from sources of ignition - No smoking. Additional guidance on fire and explosion protection may be found in various consensus standards, including NFPA 30, 69, 77 and API 2003 as well as OSHA regulation 29CFR1910.106.



CHEMICAL NAME	RESULT	ACGIH/OSHA
Aliphatic Amine	STEL	No data available
	TWA	0.100000 mg/m ³ (OSHA, ACGIH, NIOSH)
	PEL	No data available

•Special note for exposure control: consult local authorities for further acceptable exposure limits.

ENGINEERING MEASURES/CONTROLS

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts, and thermal decomposition products below appropriate airborne concentration standards and guidelines. A safety shower and eye wash fountain should be readily available. To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination. Curing ovens must be ventilated to prevent the build-up of explosive atmospheres and to prevent off-gases from entering the workplace.

ENVIRONMENTAL EXPOSURE CONTROLS

Avoid release to the environment. Construct a dike to prevent spreading of spills. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters, or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

HYGIENE MEASURES

Wash hands, forearms, and face thoroughly after handling chemical products, before eating and drinking, smoking, or using the lavatory, and at the end of the working period. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Keep away from foodstuffs, beverages, and feed.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY

In case of inadequate ventilation, wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use positive pressure supplied air respirator when airborne concentrations are not known, when airborne levels are 10 times the appropriate TLV, and when spraying is performed or product is applied by aerosol in a confined space or area with limited ventilation. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Contact health and safety professional or manufacturer for specific information.

EYE/FACE

Use chemical-resistant goggles. Chemical safety goggles in combination with a full face shield (8-inch minimum) must be used if a splash hazard exists. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU). Contact lenses should not be worn.

**HANDS**

Use permeation resistant gloves such as neoprene or nitrile. The glove must be impermeable and resistant to the product/the substance/the preparation. Selection of the glove material does not only depend on the material, but also on its quality and varies from manufacturer to manufacturer. The resistance of the glove material and manufacture must be determined in advance of the application/use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

SKIN/BODY

Wear rubber or plastic apron and permeation-resistant clothing, chemical-resistant gloves, and long-sleeved shirts, and pants. Gloves must be inspected prior to use. Remove and wash contaminated clothing before reuse.

GENERAL HYGIENE CONSIDERATIONS

Keep away from food and drink. Wash hands and face after use. Educate and train workers in the safe use and handling of this product. Emergency showers and eye wash stations should be available. Follow all label instructions.

ABBREVIATIONS KEY

- ACGIH** = American Conference of Governmental Industrial Hygiene
- MSHA** = Mine Safety and Health Administration
- NIOSH** = National Institute of Occupational Safety and Health
- OSHA** = Occupational Safety and Health Administration
- STEL** = Short Term Exposure Limits are based on 15 minute exposures
- TWA** = Time-Weighted Averages are based on 8h/day 40hr/week exposures



APPEARANCE:	Liquid, amber
ODOR:	Characteristic amine
MELTING/FREEZING POINT:	N/A
INITIAL BOILING POINT AND BOILING RANGE:	212° F
EVAPORATION RATE	N/A
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:	Not applicable
AUTO-IGNITION TEMPERATURE:	Not applicable
VAPOR PRESSURE (25°C)	<5.00 mmHg at 70° F (21° C)
VAPOR DENSITY:	N/A
DENSITY (NOMINAL):	68.047 lb/ft ³ (1.09 g/cm ³) at 70° F (21° C)
SOLUBILITY(IES) IN WATER:	Soluble > 500 g/L
VOLATILE ORGANIC COMPOUNDS:	<1 g/L



REACTIVITY:	Data not available
CHEMICAL STABILITY:	Stable under recommended storage conditions
POSSIBILITY OF HAZARDOUS REACTIONS:	May react with catalysts, oxidizing agents, peroxides, strong alkali and other radical forming substances
CONDITIONS TO AVOID:	Avoid oxidizing agents
INCOMPATIBLE MATERIALS:	Strong bases, strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide, and nitrogen oxides



ACUTE TOXICITY

For aliphatic amine:

LD50 Oral Rat 1040 mg/kg
(OCED Test Guideline 401)
LC50 Inhalation Rat 2.4 mg/l (4h)

For Alkyletheramine:

LD50 Oral Rat 1030 mg/kg
(OCED Test Guideline 401)

For Isophorone Diamine:

LD50 Oral Rat 1,030 mg/kg

OTHER INFORMATION

On the skin:

Cause effect on skin and mucous membranes.

On the eye:

Strong caustic effect

SENSITIZATION

-Sensitization possible through skin contact.

-Sensitization effect through inhalation is possibly by prolonged and repeated exposure.

CARCINOGENICITY

This product does not contain a component that is classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification: IARC, NTP, and OSHA: No component of this product present at levels greater than or equal to 0.1 % is identified as probable, possible or confirmed human carcinogen.

REPRODUCTIVE TOXICITY	Presumed human reproductive toxicant
SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE	No data available
SPECIFIC TARGET ORGAN TOXICITY-REPEATED EXPOSURE	No data available
ASPIRATION HAZARD	No data available
ADDITIONAL INFORMATION	RTECS: WH7000000

To the best of our knowledge the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

TOXICITY STUDIES:

Bisphenol A-(epichlorhydrin), Bisphenol A epoxy resin

ACUTE ORAL TOXICITY:

Low toxicity, LD50>2000 mg/kg

ACUTE DERMAL TOXICITY:

Low toxicity, LD50>2000 mg/kg

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Pre-existing skin disorders may be aggravated by over-exposure to this product

**TOXICITY:**

This product is harmful to the environment. Very toxic to fish and other aquatic life with long-lasting effects.

PERSISTENCE AND DEGRADABILITY:

According to the results of tests of biodegradability, this product is partly biodegradable.

BIOACCUMULATIVE POTENTIAL:

Although the product is partly biodegradable, significant residuals remain.

OTHER ADVERSE EFFECTS:

No data available



WASTE DISPOSAL:

- Dispose in accordance with federal, state, and local regulations.
- The generation of waste should be avoided or minimized wherever possible. Empty containers should be taken to an approved waste handling site for recycling or disposal. Incineration or landfill should only be considered when recycling is not feasible. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers).

EMPTY CONTAINER PRECAUTIONS:

- Dispose of as unused product. Do not heat or cut container with electric or gas torch. Recondition or dispose of empty container in accordance with governmental laws and regulations. Do not reuse empty container without proper cleaning. Label precautions also apply to this container when empty.
- Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Avoid dispersal of spilled material and run-off and contact with soil, waterways, drains, and sewers.



DANGER



	UN Number	UN Proper Shipping Name	Transport Hazard Class(es)	Packing Group	Environmental Hazards
DOT	UN2735	Polyamines, liquid, corrosive, n.o.s. (Isophorone Diamine)	8	III	Marine Pollutant
IMO/IMDG	UN2735	Polyamines, liquid, corrosive, n.o.s. (Isophorone Diamine)	8	III	Marine Pollutant
IATA/CAO	UN2735	Polyamines, liquid, corrosive, n.o.s. (Isophorone Diamine)	8	III	Marine Pollutant

- Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code



COUNTRY	REGULATORY LIST	NOTIFICATION
USA	TSCA	listed/registered
EU	EINECS	listed/registered
Canada	DSL	listed/registered
China	SEPA	listed/registered
Japan	ENCS	listed/registered

US FEDERAL REGULATIONS

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities: None

U.S. - SARA - Section 311/312 Hazard Categories: None

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPOs: None

U.S. - CERCLA/SARA - Section 313 - Emissions Reporting: None

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing: None

U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components: None

U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 372.65) Supplier Notification Required Components: None

U.S. Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261): Under RCRA it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

U.S. STATE REGULATIONS

California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)



WARNING:

This product can expose you to parachlorobenzotrifluoride (PCBTF), which is known to the State of California to cause cancer.

Based on information provided by Leggari suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716, File No. S7-40-10, Date 08-22-212).



HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS):

SCALE 0-4

- 4 Severe Hazard
- 3 Serious Hazard
- 2 Moderate Hazard
- 1 Slight Hazard
- 0 Minimal hazard

	NPFA	HMIS
HEALTH	3	3
FLAMMABILITY	1	1
REACTIVITY	0	0

Prepared by:

LEGGARI PRODUCTS LLC

Revision Date:

JANUARY 2022

DISCLAIMER:

Leggari Products, LLC believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Leggari Products, LLC makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.