# LEGGARI CASTING RESIN Part B Safety Data Sheet

# **Table of Contents**

Product Identification
Hazard Identification
Composition/Information on Ingredients 2
First-Aid Measures
Fire-Fighting Measures
Accidental Release Measures
Handling and Storage
Exposure Controls/Personal Protection
Physical and Chemical Properties
Stability and Reactivity
Toxicological Information
Ecological Information
Disposal Considerations
Transport Information
Regulatory Information
Other Information



### 1 PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED):

SUPPLIER/MANUFACTURER'S NAME:

ADDRESS:

TELEPHONE: EMAIL:

EMERGENCY NUMBER:

# 2 | HAZARD IDENTIFICATION

### **CLASSIFICATION**

Acute aquatic toxicity:	Category 2	Chronic aquatic toxicity:	Category 2
Acute toxicity Dermal:	Category 4	Serious eye damage:	Category 1
Acute toxicity Oral:	Category 4	Skin irritation:	Category 3

### **PICTOGRAMS**



### HAZARDOUS STATEMENTS

#### Health

- H312 Harmful in contact with skin
- H302 Harmful if swallowed
- H318 Causes serious eye damage
- H316 Causes mild skin irritation

#### Environmental

H411 - Toxic to aquatic life with long lasting effects

### **PRECAUTIONARY STATEMENTS**

#### General

- P101 If medical advice is needed, have product container or label at hand
- P102 Keep out of reach of children
- P103 Read label before use

#### Prevention

- P273 Avoid release to the environment
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P264 Wash thoroughly after handling
- P270 Do not eat, drink or smoke when using this product

### Response

- P302 + P352 IF ON SKIN: Wash with plenty of water
- P312 Call a POISON CENTER/doctor if you feel unwell
- P321 Specific treatment (see section 4 on this SDS)
- P362 + P364 Take off contaminated clothing. And wash it before reuse
- P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell
- P330 Rinse mouth.
- P391 Collect spillage.



LEGGARI CASTING RESIN PART B

LEGGARI PRODUCTS, LLC

3105 E AINSWORTH AVE WAREHOUSE 5, BAY 2 PASCO, WA 99301

1-844-LEGGARI (534-4274) CUSTOMERSERVICE@LEGGARI.COM

800-424-9300



P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor. P332 + P313 - If skin irritation occurs: Get medical advice/attention.

#### **Precautionary Statements - Storage**

No precautionary statement available.

#### **Precautionary Statements - Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant.

# 3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS	No.	% by Weight
TRIMETHYLOLPROPANE TR (PROPYLENEGLYCOL), AMINE TERMINATED) E	IS(POLY 0039	9423-51-3	65% - 100%

\* Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## 4 FIRST-AID MEASURES

#### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing - If exposed/feel unwell/concerned: Call a POISON CENTER/doctor.

#### Skin contact

Rinse/wash with lukewarm, gently flowing water and mild soap for 15-20 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

- IF exposed or concerned: Get medical advice/attention.

#### Eye contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

#### Ingestion

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

- Give 3 or 4 glasses of milk or water to drink. Never give anything by mouth to an unconscious person.

## 5 | FIRE-FIGHTING MEASURES

#### Suitable Extinguishing media

Dry chemical, foam, carbon dioxide water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

#### Unsuitable extinguishing media

If water is used, use very large quantities of cold water.

#### Special hazards in case of fire

Excessive pressure or temperature may cause explosive rupture of containers.

#### Fire-fighting procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

-Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### Special protective actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear. Care should always be exercised in dust/mist areas.









#### Emergency procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). DO NOT touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

-If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

#### **Recommended equipment**

Appropriate dust or face mask to eliminate breathing foam dust particulates.

#### **Personal Precautions**

Avoid breathing vapors. Avoid contact with skin, eyes or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

#### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

#### Methods and materials for containment and cleaning up

Soak up material with absorbent and shovel into a chemical waste container. Cover container, but do not seal, and remove from work area. Residues from spill cleanup may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, call CHEMTREC (Chemical Transportation Emergency Center) at 800-424-9300.

# 7 HANDLING AND STORAGE

#### General

- Wash hands after use
- Do not get in eyes, on skin or on clothing.
- Do not breathe vapors or mists.
- Use good personal hygiene practices.
- Eating, drinking and smoking in work areas is prohibited.
- Remove contaminated clothing and protective equipment before entering eating areas.
- Eyewash stations and showers should be available in areas where this material is used and stored.
- Individuals with existing respiratory disease such as chronic bronchitis, emphysema, or asthma should not be exposed.

#### Ventilation requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

#### Storage room requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

-Store in tightly sealed containers to protect from atmospheric moisture. Store in a cool dry area. Store liquid in containers above ground and surround by dikes to contain spills or leaks.

-Do not cut, drill, grind, weld, or perform similar operations on or near containers.

### 8

### **EXPOSURE CONTROLS/PERSONAL PROTECTION**



#### Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. - If additional protection is needed for entire face, use in combination with a face shield.

#### Skin protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over- boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

#### **Respiratory protection**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program

that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. - In poorly ventilated areas, a cartridge mask NIOSH approved for organic vapors is recommended under the following conditions: emergency situations, when product vapor concentration is greater than 20 ppm for a period longer than 15 min., during repair and cleaning of equipment, during transfer or discharge of the product.

#### Appropriate engineering controls

9

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

### PHYSICAL AND CHEMICAL PROPERTIES

Density:	7.89 lb/gal	Lower explosion level:	N.A.
Specific gravity:	.95	Upper explosion level:	N.A.
VOC regulatory:	0.00 lb/gal	Vapor pressure:	N.A.
VOC part A & B Combined:	N.A.	Vapor density:	Heavier than air
Appearance:	Liquid	Freezing point:	N.A.
Odor threshold:	N.A.	Melting point:	N.A.
Odor description:	Amine-like	Low boiling point:	N.A.
Ph:	N.A.	High boiling point:	N.A.
Water solubility:	N.A.	Auto ignition temp:	N.A.
Flammability:	N.A.	Decomposition pt. :	N.A.
Flash Point Symbol:	N.A.	Evaporation rate:	Slower than ether
Flash Point:	200° C	Coefficient water/oil:	N.A.
Viscosity:	N.A.		

### 10 STABILITY AND REACTIVITY

#### Stability

Material is stable at standard temperature and pressure.

#### **Conditions to avoid**

Heat, high temperature, open flame, sparks, and moisture. Contact with incompatible materials in a closed system will cause buildup of pressure.

#### Hazardous reactions/polymerization

Will not occur.

#### Incompatible materials

This product will react with epoxies, isocyanates, and strong oxidizing agents. Some reactions can be violent.

#### Hazardous decomposition products

Combustion products: organic vapors and thermal decomposition fragments.

### 11 TOXICOLOGIAL INFORMATION

#### Skin Corrosion/Irritation

Causes mild skin irritation

#### Serious Eye Damage/Irritation

Any contact should not be left untreated. Causes serious eye damage

#### **Respiratory/Skin Sensitization**

Exposure may cause mucous membrane and respiratory tract irritation, tightness of chest, headache, shortness of breath, and a dry cough. The effects of acute exposure may be delayed in onset up to 12-24 hours. Repeated exposure above current occupational limits may cause an allergic sensitization of the respiratory tract. This is characterized by an asthma-like response upon re-exposure to the chemical. The symptoms may include coughing, wheezing, shortness of breath and chest tightness.







- Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

#### **Reproductive Toxicity**

Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity - Repeated Exposure

Repeated exposure generally aggravates the following medical conditions : Cardiovascular disease and Chronic respiratory disease. - Based on available data, the classification criteria are not met.

#### Aspiration Hazard

Based on available data, the classification criteria are not met.

#### **Acute Toxicity**

If ingested : In humans, irritation or chemical burns of the mouth, pharynx, esophagus and stomach can develop following ingestion, and injury may be severe and cause death.

- Harmful in contact with skin

- Harmful if swallowed

#### Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

## 12 ECOLOGICAL INFORMATION

Toxicity	Toxic to aquatic life Toxic to aquatic life with long lasting effects	
Persistence and Degradability	No data available	
Bioaccumulative Potential	No data available	
Mobility in Soil	No data available	
Other Adverse Effects	No data available	
Bioaccumulative Potential	No data available	

### 13 DISPOSAL CONSIDERATIONS

#### WASTE DISPOSAL:

Under RCRA, it is the responsibility of the user of the product, to determine a the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

### 14 TRANSPORT INFORMATION

#### **U.S. DOT INFORMATION**

UN/NA #: 3082

UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TRIMETHYLOLPROPANE TRIS ETHER)

Hazard Class:	9
Packing Group:	Ш
Placard:	Class 9





### **IMDG INFORMATION**

UN/NA #: 3082

UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TRIMETHYLOLPROPANE TRIS ETHER)

Hazard Class:	9
Packing Group:	ш
Placard: Class	9
Marine Pollutant:	Yes

#### IATA INFORMATION UN/NA #: 3082

UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TRIMETHYLOLPROPANE TRIS ETHER)

Hazard Class:	9
Packing Group:	ш
Placard: Class	Class 9

# 5 REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0039423-51-3	TRIMETHYLOLPROPANE TRIS(POLY (PROPYLENE GLYCOL), AMINE TERMINATED) ETHER	65% - 100%	DSL, SARA312, VOC, TSCA

# 16 OTHER INFORMATION



As per GHS, category 1 is the greatest level of hazard within each class.

#### GLOSSARY

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; CA Prop65- California Proposition 65; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL -Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

Prepared by: Revision Date:

LEGGARI PRODUCTS LLC JANUARY 1, 2023

#### **DISCLAIMER:**

Leggari Products, LLC believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Leggari Products, LLC makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

